

### Transparente c/ Espiral Verde ou Azul

#### Serviço Leve

Indicada para serviços leves de sucção e descarga, para os setores de Irrigação Agrícola e Construção Civil.  
Temperatura de Trabalho: +5°C ~ +50°C (PVC).



DIÂMETRO NOMINAL	DIÂMETRO INTERNO	DIÂMETRO EXTERNO	PRESSÃO DE TRABALHO		PRESSÃO DE RUPTURA		VÁCUO	RAIO DE CURVATURA	LANÇE
			25°C	25°C	25°C	25°C			
pol.	mm	mm	kgf/cm <sup>2</sup>	lbf/pol <sup>2</sup>	kgf/cm <sup>2</sup>	lbf/pol <sup>2</sup>	mmHg	Trabalho - Mínimo 25°C mm	m
1"	25,0	31,6	4,9	70	14,8	211	700	195	25 / 50
1.1/4"	31,5	37,8	4,2	60	12,7	181	680	240	25 / 50
1.1/2"	38,0	45,6	4,2	60	12,7	181	650	285	25 / 50
2"	50,0	58,7	4,1	58	12,0	175	600	300	25 / 50
* 2.1/2"	62,5	72,0	3,8	55	11,5	164	580	360	25 / 50
* 3"	75,5	85,6	3,3	47	10,0	142	500	400	25 / 50
* 4"	101,9	112,3	2,3	33	7,0	100	450	480	25 / 50
* 5"	127,9	139,0	1,8	26	5,5	78	420	500	15 / 30
* 6"	150,0	164,4	1,7	24	5,0	71	350	620	15 / 30
* 8"	204,0	220,5	1,3	19	4,0	57	270	1560	15 / 30
* 10"	254,0	273,0	1,2	17	3,5	50	180	1800	6 / 12
* 12"	305,0	324,0	1,0	14	3,0	42	100	2200	6 / 12

\* Fornecimento sob consulta

### Transparente con Espiral Verde o Azul

#### Servicio Liviano

Para servicios muy livianos de succión y descarga, para los sectores de Riego Agrícola y Construcción Civi.  
Temperatura del Trabajo: +5°C ~ +50°C (PVC).



DIÂMETRO NOMINAL	DIÂMETRO INTERIOR	DIÂMETRO EXTERIOR	PRESIÓN DE TRABAJO		PRESIÓN DE RUPTURA		VACÍO	RADIO DE CURVATURA	LARGO
			25°C	25°C	25°C	25°C			
pul.	mm	mm	kgf/cm <sup>2</sup>	lbf/pul <sup>2</sup>	kgf/cm <sup>2</sup>	lbf/pul <sup>2</sup>	mmHg	Trabalho - Mínimo 25°C mm	m
1"	25,0	31,6	4,9	70	14,8	211	700	195	25 / 50
1.1/4"	31,5	37,8	4,2	60	12,7	181	680	240	25 / 50
1.1/2"	38,0	45,6	4,2	60	12,7	181	650	285	25 / 50
2"	50,0	58,7	4,1	58	12,0	175	600	300	25 / 50
2.1/2"	62,5	72,0	3,8	55	11,5	164	580	360	25 / 50
3"	75,5	85,6	3,3	47	10,0	142	500	400	25 / 50
4"	101,9	112,3	2,3	33	7,0	100	450	480	25 / 50
5"	127,9	139,0	1,8	26	5,5	78	420	500	15 / 30
6"	150,0	164,4	1,7	24	5,0	71	350	620	15 / 30
8"	204,0	220,5	1,3	19	4,0	57	270	1560	15 / 30
10"	254,0	273,0	1,2	17	3,5	50	180	1800	6 / 12
12"	305,0	324,0	1,0	14	3,0	42	100	2200	6 / 12

### Transparent with Green or Blue

#### Light Jobs

Recommended for light Jobs of suction or discharge, for the Agricultural Irrigation and Civil Construction sectors.  
Work temperature: +5°C ~ +50°C (PVC).



NOMINAL DIAMETER	INTERNAL DIAMETER	EXTERNAL DIAMETER	WORK PRESSURE		BURST PRESSURE		VACUUM	BEND RADIUS	LENGTH
			25°C	25°C	25°C	25°C			
inches	mm	mm	kgf/cm <sup>2</sup>	psi	kgf/cm <sup>2</sup>	psi	mmHg	Minimum Working 25°C mm	m
1"	25,0	31,6	4,9	70	14,8	211	700	195	25 / 50
1.1/4"	31,5	37,8	4,2	60	12,7	181	680	240	25 / 50
1.1/2"	38,0	45,6	4,2	60	12,7	181	650	285	25 / 50
2"	50,0	58,7	4,1	58	12,0	175	600	300	25 / 50
2.1/2"	62,5	72,0	3,8	55	11,5	164	580	360	25 / 50
3"	75,5	85,6	3,3	47	10,0	142	500	400	25 / 50
4"	101,9	112,3	2,3	33	7,0	100	450	480	25 / 50
5"	127,9	139,0	1,8	26	5,5	78	420	500	15 / 30
6"	150,0	164,4	1,7	24	5,0	71	350	620	15 / 30
8"	204,0	220,5	1,3	19	4,0	57	270	1560	15 / 30
10"	254,0	273,0	1,2	17	3,5	50	180	1800	6 / 12
12"	305,0	324,0	1,0	14	3,0	42	100	2200	6 / 12