



Marrom com Fio Antiestático

Indicada para sucção e descarga de produtos derivados de petróleo, bem como grande variedade de produtos químicos. Também é indicada para carga e descarga de produtos altamente inflamáveis devido possuir fio antiestático. Temperatura de Trabalho: +5°C ~ +50°C (PVC).



	DIÂMETRO NOMINAL	DIÂMETRO INTERNO	DIÂMETRO EXTERNO	PRESSÃO DE TRABALHO 25°C		PRESSÃO DE RUPTURA 25°C		VÁCUO 25°C	RAIO DE CURVATURA Trabalho - Mínimo 25°C	LANCE
	pol.	mm	mm	kgf/cm ²	lbf/pol ²	kgf/cm ²	lbf/pol ²	mmHg	mm	m
*	1"	25,0	32,0	8,0	114	24,0	341	760	475	25 / 50
*	1.1/4"	31,5	39,0	7,3	104	22,0	313	760	500	25 / 50
*	1.1/2"	38,0	46,0	6,7	95	20,0	284	760	550	25 / 50
*	2"	50,0	59,5	6,0	85	18,0	256	760	775	25 / 50
*	2.1/2"	62,5	73,0	6,0	85	18,0	256	760	875	25 / 50
*	3"	74,5	86,0	6,0	85	18,0	256	760	1.425	25 / 50
*	4"	101,2	115,0	5,0	71	15,0	213	760	1.750	25 / 50
*	5"	127,0	140,0	4,0	57	12,0	171	760	2.475	15 / 30
*	6"	149,0	164,0	3,7	52	11,0	156	760	2.750	15 / 30
*	8"	204,0	224,4	3,7	52	11,0	156	750	4.250	15 / 30

* Fornecimento sob consulta

Marrón con Hilo Antiestático

Para succión y descarga de productos derivados del petróleo, así como una amplia variedad de productos químicos. Para carga y descarga de productos altamente inflamables. Temperatura del Trabajo: +5°C ~ +50°C (PVC).



	DIÂMETRO NOMINAL	DIÂMETRO INTERIOR	DIÂMETRO EXTERIOR	PRESIÓN DE TRABAJO 25°C		PRESIÓN DE RUPTURA 25°C		VACIO 25°C	RAIO DE CURVATURA Trabajo - Mínimo 25°C	LARGO
	pul.	mm	mm	kgf/cm ²	lbf/pul ²	kgf/cm ²	lbf/pul ²	mmHg	mm	m
	1"	25,0	32,0	8,0	114	24,0	341	760	475	25 / 50
	1.1/4"	31,5	39,0	7,3	104	22,0	313	760	500	25 / 50
	1.1/2"	38,0	46,0	6,7	95	20,0	284	760	550	25 / 50
	2"	50,0	59,5	6,0	85	18,0	256	760	775	25 / 50
	2.1/2"	62,5	73,0	6,0	85	18,0	256	760	875	25 / 50
	3"	74,5	86,0	6,0	85	18,0	256	760	1.425	25 / 50
	4"	101,2	115,0	5,0	71	15,0	213	760	1.750	25 / 50
	5"	127,0	140,0	4,0	57	12,0	171	760	2.475	15 / 30
	6"	149,0	164,0	3,7	52	11,0	156	760	2.750	15 / 30
	8"	204,0	224,4	3,7	52	11,0	156	750	4.250	15 / 30

Brown with Anti-static Wire

Recommended for suction and discharge of petroleum - based products, as well as a wide scope of chemicals. Recommended for loading and discharging highly flammable products. Work temperature: +5°C ~ +50°C (PVC).



	NOMINAL DIAMETER	INTERNAL DIAMETER	EXTERNAL DIAMETER	WORK PRESSURE 25°C		BURST PRESSURE 25°C		VACUUM 25°C	BEND RADIUS Working - Minimum 25°C	LENGTH
	inches	mm	mm	kgf/cm ²	psi	kgf/cm ²	psi	mmHg	mm	m
	1"	25,0	32,0	8,0	114	24,0	341	760	475	25 / 50
	1.1/4"	31,5	39,0	7,3	104	22,0	313	760	500	25 / 50
	1.1/2"	38,0	46,0	6,7	95	20,0	284	760	550	25 / 50
	2"	50,0	59,5	6,0	85	18,0	256	760	775	25 / 50
	2.1/2"	62,5	73,0	6,0	85	18,0	256	760	875	25 / 50
	3"	74,5	86,0	6,0	85	18,0	256	760	1.425	25 / 50
	4"	101,2	115,0	5,0	71	15,0	213	760	1.750	25 / 50
	5"	127,0	140,0	4,0	57	12,0	171	760	2.475	15 / 30
	6"	149,0	164,0	3,7	52	11,0	156	760	2.750	15 / 30
	8"	204,0	224,4	3,7	52	11,0	156	750	4.250	15 / 30