

KANASPRAY

Preta

Manguera de PVC reforçada com fios sintéticos utilizada em pivôs de irrigação. Leve e flexível, possui boa resistência à abrasão e intempéries. Temperatura de Trabalho: +5°C ~ +50°C (PVC).



DIÂMETRO NOMINAL	DIÂMETRO INTERNO	DIÂMETRO EXTERNO	PRESSÃO DE TRABALHO		PRESSÃO DE RUPTURA		LANÇE
pol.	mm	mm	kgf/cm ²	lbf/pol ²	kgf/cm ²	lbf/pol ²	m
3/4"	20,5	25,5	7	100	21	300	50

Negra

Manguera de PVC reforçada con hilos sintéticos utilizada en pivotes de riego. Ligero y flexible, posee buena resistencia a la abrasión e intemperie. Temperatura del Trabajo: +5°C ~ +50°C (PVC).



DIÂMETRO NOMINAL	DIÂMETRO INTERIOR	DIÂMETRO EXTERIOR	PRESIÓN DE TRABAJO		PRESIÓN DE RUPTURA		LARGO
pol.	mm	mm	kgf/cm ²	lbf/pol ²	kgf/cm ²	lbf/pol ²	m
3/4"	20,5	25,5	7	100	21	300	50

Black

Reinforced PVC hose with synthetic threads used in irrigation pivots. Lightweight and flexible, it has good resistance to abrasion and bad weather. Work temperature: +5°C ~ +50°C (PVC).



NOMINAL DIAMETER	INTERNAL DIAMETER	EXTERNAL DIAMETER	WORK PRESSURE		BURST PRESSURE		LENGTH
inches	mm	mm	kgf/cm ²	psi	kgf/cm ²	psi	m
3/4"	20,5	25,5	7	100	21	300	50